

HDA500-G - 5.0" WVGA TFT



Der amerikanische Hersteller Hantronix bietet eine große Auswahl an TFT Displays in den Größen von 2,4" bis 10,4".

Der Hersteller hat sich verpflichtet, alle Modelle langfristig, d.h. über mehrere Jahre zu liefern. Damit sind diese Displays auch für den industriellen Markt ideal.

Alle Module verfügen über eine weiße LED-Hintergrundbeleuchtung. Displays unter 3,5" besitzen einen integrierten Displaycontroller.

Hantronix fertigt neben TFTs auch alle Arten von Passiv-Displays, sowohl standard Grafik- und Textdisplays als auch Kundenspezifische LCDs.

HDA700L-G - 7" WVGA TFT



Size	PART NUMBER	Resolution	Colors	Viewing Angle	Dimensions	Active Area	Brightness	Contrast	Operating Temperature	Interface	Backlight	Optional	Features
Inch		Pixel		U/D/R/L	WxHxT mm	WxH mm	cd/m ²	typ.					
3.5"	HDA350-2G	320 x 240	16.7M	50/60/60/60	76.9 x 63.9 x 3.3	70.08 x 52.56	300	300:1	-20°C to +70°C	24 Bit RGB	LED	Touch	-
3.5"	HDA350-2GH	320 x 240	16.7M	50/60/60/60	76.9 x 63.9 x 3.3	70.08 x 52.56	800	450:1	-20°C to +70°C	24 Bit RGB	LED	Touch	High Brightness
4.3"	HDA430-3G	480 x 272	16.7M	40/50/60/60	105.5 x 67.2 x 3.95	95.04 x 53.85	500	450:1	-20°C to +70°C	24 Bit RGB	LED	Touch	-
4.3"	HDA430-3GH-1	480 x 272	16.7M	50/60/65/65	105.5 x 67.2 x 3.95	95.04 x 53.85	1000	350:1	-20°C to +70°C	24 Bit RGB	LED	Touch	High Brightness
5.0"	HDA500-G	800 x 480	16.7M	60/70/70/70	118.5 x 77.55 x 3.4	108 x 64.8	310	400:1	-20°C to +70°C	24 Bit RGB	LED	Touch	High Resolution
5.7"	HDA570S-V	320 x 240	262K	55/50/60/60	144.0 x 104.6 x 13.0	115.2 x 86.4	380	450:1	-20°C to +70°C	18 Bit RGB	LED	Touch	-
5.7"	HDA570S-VH	320 x 240	262K	60/50/60/60	144.0 x 104.6 x 13.0	115.2 x 86.4	700	450:1	-20°C to +70°C	18 Bit RGB	LED	Touch	High Brightness
5.7"	HDA570V-G	640 x 480	262K	50/65/65/65	144.0 x 104.6 x 13.0	115.2 x 86.4	380	450:1	-20°C to +70°C	18 Bit RGB	LED	Touch	-
5.7"	HDA570V-GH	640 x 480	262K	55/65/65/65	144.0 x 104.6 x 13.0	115.2 x 86.4	900	500:1	-20°C to +70°C	18 Bit RGB	LED	Touch	High Brightness
5.7"	HDA570V-GHL	640 x 480	262K	55/65/65/65	144.0 x 104.6 x 13.0	115.2 x 86.4	900	500:1	-20°C to +70°C	LVDS	LED	Touch	High Brightness
7.0"	HDA700L-2G	800 x 480	262K	50/60/70/70	165.0 x 104.0 x 5.4	153.6 x 86.64	350	500:1	-20°C to +70°C	18 Bit RGB	LED	Touch	-
7.0"	HDA700L-3G	800 x 480	262K	50/60/70/70	165.0 x 104.0 x 5.4	153.6 x 86.64	350	500:1	-20°C to +70°C	18 Bit RGB	LED	Touch	Built in LED Driver
7.0"	HDA700L-G	800 x 480	262K	55/65/65/65	166.6 x 109.4 x 10.0	152.4 x 91.44	500	250:1	-20°C to +70°C	18 Bit RGB	LED	Touch	-
7.0"	HDA700L-GH	800 x 480	262K	55/65/65/65	166.6 x 109.4 x 10.0	152.4 x 91.44	1000	250:1	-20°C to +70°C	18 Bit RGB	LED	Touch	High Brightness
7.0"	HDA700L-GHL	800 x 480	262K	55/65/65/65	166.6 x 109.4 x 10.0	152.4 x 91.44	1000	250:1	-20°C to +70°C	LVDS	LED	Touch	High Brightness
8.0"	HDA800S-GT	800 x 600	262K	50/75/70/70	183.0 x 141.0 x 5.0	162 x 121.5	400	500:1	-20°C to +70°C	18 Bit RGB	LED	Touch	-
8.0"	HDA800S-GL	800 x 600	262K	50/75/70/70	183.0 x 141.0 x 5.8	162 x 121.5	400	500:1	-20°C to +70°C	LVDS	LED	Touch	-
8.0"	HDA800S-GHL	800 x 600	262K	50/75/70/70	176.3 x 138.2 x 7.8	162.0 x 121.5	1300	500:1	-20°C to +70°C	LVDS	LED	Touch	High Brightness
10.4"	HDA1040S	800 x 600	262K	45/65/65/65	236.0 x 176.9 x 5.6	211.2 x 158.4	400	400:1	-20°C to +70°C	LVDS	LED	Touch	-